

# IMPORTANT INSTRUCTIONS

# LS343

STAINLESS STEEL



## For opening & re-sealing fixture with recessed lid

Thank you for taking the time to read this, it will save you time and money.

First, some simple rules.

**Do not use your battery drill**

**Do not use silicone sealant**

**Keep all surfaces clean**

**keep all foreign material out of the fixture**

**1. Clear area around fixture of loose dirt and debris, and wipe the fixture off with clean rag**



**2. Clean out socket head screws with a small pointed object**



**3. Ensure allen-key is in good condition and loosen each screw one turn only, repeat once again and then just remove each screw**



**4. Use allen-key to lift off cover**

**5. Place lid up-side-down on clean rag**



**6. Clean out rim, remove any foreign objects from fixture**



**7. Run Fixture.**

Allow to burn for 10-15 minutes without lid attached to allow any moisture in fixture to evaporate.



**10-15 MIN.**



**LUMASCAPE**  
USA

**LUMASCAPE USA INC.**

US Head Office  
1300 Industrial Rd., Unit #19  
San Carlos, CA 94070  
USA

Telephone  
1-(650)-595-LUMA(5862)

Fax  
1-(650)-595-5820

[www.lumascape.com](http://www.lumascape.com)

**Free Call**  
**1-866-695-LUMA(5862)**  
(US & Canada)

# IMPORTANT INSTRUCTIONS

# LS343

STAINLESS STEEL

## B

### For opening & re-sealing fixture with recessed lid

8. Wipe seal clean, if necessary disassemble the seal and wash in clean water then dry thoroughly



9. Ensure glass bevel faces top of lid so that the glass and trim are flush



10. Insert 5 screws all the way into cover, leaving one hole without screw. Place allen-key in 6th cover hole



11. Ensure cover is inside the lip at the edge of the seal



12. Place cover on fixture lining up allen-key with any hole



13. Push lid down evenly ensuring allen-key remains vertical (at 90degrees to the cover)

14. Start each of the screws. If the cover has been lined up correctly, these screws will start very easily. Remove allen-key and insert 6th screw



15. Progressively tighten, no torque pattern is required, just keep going around until all screws are tight and the glass, trim and edge of fixture are flush.



Do not attempt to tighten any one screw fully, This will take longer and will not seat the seal properly.



**LUMASCAPE USA INC.**

US Head Office  
1300 Industrial Rd., Unit #19  
San Carlos, CA 94070  
USA

Telephone  
1-(650)-595-LUMA(5862)

Fax  
1-(650)-595-5820

[www.lumascape.com](http://www.lumascape.com)

Free Call  
**1-866-695-LUMA(5862)**  
(US & Canada)